Kompac[®] FUJ!FILM_ Phoenix

Available in 30" Widths

Two cutting edge platforms leading the way for the printing & coating industry

Phoenix 30 with interface conveyor, shown with Fuji J Press 750S Sheetfed Inkjet Press

- Powerful UV: Up to 400watts/inch
- Kompac Vac: For quick and effortless 2-minute coating change & clean up
- Coating Sensor: Automatically detects coating level & replenishes as needed
- IR Dryer: Dries Aqueous coatings and assists UV coating wet-out for increased gloss levels (Optional)

FURFILM

- Sheet Detection: Sheet monitoring system helps prevent fires and tracks sheet counts (Optional)
- Interface Conveyor: Allows for inline coating on select digital and offset presses (Optional)
- High Pile Feeder: Pallet/Dolly loadable feeder for high volume feeding (Optional)
- High Pile Stacker: Pallet/Dolly loadable stacker for high volume stacking (Optional)
- Duplexer: For double-sided coating (Optional)
- Anilox Coating System: Mounts on top of coater (for running Matte, Soft Touch, AQ & specialty coatings)(Optional)
- Corona Treating: For plastic, synthetic, and metalized substrates (Optional)
- Air Curtain: (cools sheet helps to prevent blocking/picking) (Optional)
- Safety Light Curtains: Mounted on the Feeder and/or Stacker Prevents operator from reaching into these areas. (Optional)



Intelligent Coating Priming System

The Phoenix is a revolutionary new coating/ priming system that is the most modular system available. Our system utilizes IOTech4 allowing you to view real time statistics for information like job run time, number of impressions, coating usage, and much more. Maximize effiency and minimize operator error by tracking jobs via part number.



Phoenix 30 with interface conveyor

Kompac Technologies, LLC. 7 Commerce Street, Somerville, NJ 08876

TEL: +1 908 534 8411 FAX: +1 908 534 8412 info@kompactech.com www.kompactech.com





Specifications

Sheet Size:	
	30.5" X 30" (775MM X 762MM)
	30.5" X 40" (775MM X 1,016MM)
	30.5" X 45" (775MM X 1,143MM) (MAX.)
Sheet Thickness:	7PT to 30PT (150GSM to 600 GSM)
Speed:	► 250FPM (76M/M)
Coating Types:	UV/AQUEOUS/PRIMERS/SPECIALTY
Substrates:	PAPER/CARD STOCK/PLASTICS/SYNTHETICS

For more information about sales and service, please contact our Sales and Technical Support Representatives.

Learn more at https://www.kompactech.com/



Kompac Technologies, LLC. 7 Commerce Street, Somerville, NJ 08876

TEL: +1 908 534 8411 FAX: +1 908 534 8412 info@kompactech.com www.kompactech.com